

PRODUCT PROFILE

DESCRIPTION

The FADE BLOCK™ SUPER•COTE™ System is a superior heat-reflective, water-based exterior coating. This highly breathable system has been formulated for superior salt spray, moisture, and mildew-resistant properties. FADE BLOCK™ SUPER•COTE™ uses solar reflective, ultraviolet stable pigment, yielding longer-lasting colorfast colors.

FEATURES

- Mildew and Dirt Resistant
- Superior Fade Resistance
- Low VOC, Low Order
- Available in Satin Finish

BENEFITS

- Long-Lasting Colors
- Long-Term Protection

RECOMMENDED PRIMERS/SUBSTRATES

FADE BLOCK™ SUPER•COTE™ is recommended over HI-REFLECTIVE PRIMER (SMOOTH), HI-BUILD TEXTURED PRIMER, METAL-PRIME™ PRIMER for Metal Applications, TEX-BOND® PRIMER for plastic surfaces, and WOOD PRIMER 27 for wood surfaces.

SPECIAL QUALIFICATIONS

FADE BLOCK™ SUPER•COTE™ is a third-party verified Type III EPD (ISO 14025) product, based on product-specific and facility-specific manufacturing data; CDPH Standard Method v1.2 compliant.

PRODUCT APPLICATION

INSTALLATION

FADE BLOCK™ SUPER•COTE™ can be applied by brush, roller, or airless spray. Commercial grade airless tip size .017 to .019.

GENERAL/SURFACE PREPERATION

All surfaces must be sound, clean, and dry prior to application of FADE BLOCK™ SUPER•COTE™. All loose, flaking, or oxidized paint shall be removed from surface by abrasive-blasting, water-blasting, wire brushing, or scraping prior to priming with TEX-COTE® approved primers.

Cracks less than 1/32" shall be filled with FLEX-PATCH® compound. Cracks greater than 1/32" should be patched with cementitious patching compound. Masonry surfaces should be primed with either HI-REFLECTIVE PRIMER (SMOOTH), HI-BUILD TEXTURED PRIMER, or other approved TEX-COTE® products (Consult a TEX-COTE® Representative for primer recommendation).

For new concrete, use either HI-REFLECTIVE PRIMER (SMOOTH) or HI-BUILD TEXTURED PRIMER. Metal surfaces should be primed with METAL-PRIME™, and for plastic surfaces, TEX-BOND® PRIMER is recommended. See Technical Data for all primer information.

APPLICATION RATE

Coverage rates will be between 175-225 square feet per gallon (4.9 to 6.0 square meters/liters). Two coats are recommended at 350-450 square feet per gallon per coat depending on surface porosity and texture. Deep-tone colors may require application in two or more coats at a minimum of 300-350 square feet per gallon per coat. Some deep-tone colors may require additional product for complete coverage depending on the color. An actual mock-up should be done prior to application to determine the proper square footage per gallon for the color chosen. Spray/back roll application is recommended depending on the texture and porosity of the substrate.

APPLICATION

Apply product over a dry, clean, properly prepared surface, at the specified application rate. Application shall be at uniform film thickness over the entire wall. A wet edge shall be maintained during spraying (brushing or rolling) at all times. To prevent lap marks, avoid starting and stopping midway on walls. On large areas, two (2) or more people spraying simultaneously are recommended to avoid laps marks and spray patterns. If rolling on FADE BLOCK™ SUPER•COTE™ with fully loaded roller, apply in vertical strokes initially, then cross roll for even film, ending with vertical strokes. To prevent lap marks, proceed as above and continue to a "natural break" such as panel edge, seam or corner.

DRYING/CURING TIMES

- To Touch: Two (2) Hours at 70°F
- Dry Hard: 24 Hours Minimum

Note: After 24 Hours, the film will continue to cure with additional days for complete drying. Times are based on ideal weather conditions.



BEST PERFORMANCE

IMPORTANT STEPS

- Do not apply material when snow, rain, or freezing conditions are imminent. Wet conditions combined with cold temperatures may cause improper curing of the product.
- Application temperature shall be between 45°F rising to 100°F (7°C to 37.7°C), 5° F (3° C above dewpoint)
- Products shall be handled and stored as indicated herein.
- Roof and parapet top caps shall be installed and sealed against water penetration before application.
- DO NOT APPLY if rain is imminent.
- KEEP FROM FREEZING.
- Surfaces shall be clean, dry, and properly prepared.
- Formulated for use over HI-REFLECTIVE PRIMER (SMOOTH), HI-BUILD TEXTURED PRIMER, and other TEX-COTE® approved products.
- Trim areas, metals, and other substrates may require another TEX-COTE® primer. Consult the manufacturer or representative for recommendations.
- TEX-COTE LLC does not promote or recommend coating the sealant joints, nor is the sealant compound an approved substrate.

TECHNICAL DATA

FADE BLOCK™ SUPER•COTE™ Wall Applicable Standards | American Society for Testing Materials

TEST METHOD	PROPERTY	RESULT
ASTM D2565-99-T-1, C#4	Accelerated Weathering	5,000 Hours - PASSED
ASTM B117	Salt Spray Resistance	100 Hours - PASSED
ASTM D714	Blistering Resistance	100 Hours - PASSED
ASTM D610	Rusting Resistance	100 Hours - PASSED
ASTM D968	Abrasion Resistance	825 Liters Falling Sand
ASTM D3273/D3274	Mold & Mildew Resistance	28 Days - Rating 10, No Growth
ASTM D6904	Wind-Driven Rain Resistance	PASSED
ASTM C67/D2794	Freeze-Thaw Resistance	50 Cycles - PASSED
ASTM D4585	Humidity Resistance	100 Hours - PASSED
ASTM E96	Permeability	8.5 Perms (with Primer)
ASTM C1305	Crack Bridging	No Cracks, Separation, or Loss of Film
ASTM E-84	Surface Burning of Building Materials	Meets Class A Flame Spread Index
ASTM E-1795	Standard for Lead-Based Paint Encapsulation	PASSED All Tests for Interior & Exterior Use

TEST PROPERTY	RANGES	TEST PROPERTY	RANGES
Gloss (Satin)	10 20 @ 60°	VOC (grams/liters minus water)	<50 grams/liter
Resin Base	100% Acrylic	Volume Percent	33 - 37%
Dry Film Thickness	3-4mils	Weight Percent - Satin	40 - 51%
Wet Film Thickness	7-9 mils	Weight/Gallon (pounds)	9.3 - 10.8%

ORDER INFORMATION

**PACKAGING
COLORS
SHELF-LIFE**

Available in one (1), five (5) and fifty-five (55) gallon containers.
Over 570 fade resistant colors. Deep-tone colors incur an additional charge.
12-Month Shelf Life under proper conditions:

- Containers stored upright and airtight in a cool, dry place.
- Maintain air temperature between 45°F-100°F (7°C - 38°C). KEEP FROM FREEZING.
- Skins formed on surface of products shall be removed prior to mixing, moving, or using.



SAFETY

WARNING

- Contains hydrocarbon solvents.
- Use with adequate ventilation.
- DO NOT BREATHE spray mist or dust.
- Avoid contact with eyes, skin, and clothing.
- Wash hands thoroughly after handling.

FIRST AID

- If you experience difficulty in breathing, leave the area to obtain fresh air.
- If difficulty continues, seek medical attention.
- In case of eye contact, flush immediately with water for at least 15 minutes.
- Seek medical attention if blurring or redness occurs.

VOC COMPLIANCE

All TEX-COTE® products comply with federal Volatile Organic Compound (VOC) rules and regulations.

Please contact your nearest TEX-COTE LLC office for assistance with the local and state VOC compliance in the area of intended use.

WARRANTY

Upon completion of the application of the coating in accordance with the manufacturer's recommendations, TEX-COTE LLC will extend its limited commercial warranty for product replacement as a result of a defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with the manufacturer's recommendations for installation. TEX-COTE LLC shall have no obligation to contribute to or otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty is available upon request.



Corporate HQ & East Coast Facility

2422 E. 15th St., Panama City, FL 32405 | 800-454-0340 | 850-769-0347 | Fax 850-913-8619

South Florida Sales Office

7000 W. Palmetto Park Rd., Ste 210-W14, Boca Raton, FL 33433 | 954-581-0771 | Fax 954-581-9516

West Coast Facility

417 E. Weber Ave., Compton, CA 90222 | 323-233-3111 | Fax 310-438-2873