

TexSpray 1030 FC

The 1030 FC is our highest production sprayer for applying smooth and aggregate textures, elastomeric and acrylic materials on large concrete buildings.

High-Output Piston Texture Pump

- Uniquely designed pump with extra large passages for pumping aggregated materials
- Innovative soft seal in the foot valve ensures optimal performance
- High-output pump produces texture delivery rates to 3.0 gpm at 1000 psi for time-saving production rates

Automatic Pressure Unloader

- Ensures a soft start with each trigger pull
- Eliminates the material blast that can impact finish quality
- Puts less stress on material to prevent pack-out conditions

Wide Fan Pattern

- Up to a 4-ft (1.2-m) wide fan pattern
- Fast, consistent material coverage at a high production rate
- Fan pattern enables you to complete projects with fewer passes

Easy-to-Use Operator Controls

- Full-range flow control from .9 to 3 gpm (3.4 to 11.4 Lpm)
- Heavy-duty air regulator for precise air management

Heavy-Duty Suction Tube

- Pump directly from 5-gallon pails or 55-gallon drums

On-Board Air Filtration System

- Filters incoming air to keep your sprayer running at optimal performance
- Auto-drain design automatically removes moisture build-up




| DESCRIPTION | PART NUMBER | MAX GPM (LPM) | MAX PSI (BAR) | MAX HOSE |
|-------------|-------------|---------------|---------------|----------------|
| 1030 FC | 234113 | 3.0 (11.4) | 1000 (70) | 400 ft (122 m) |

Comes complete with: 50 ft (15 m) hose, Heavy Duty Texture Gun, and 4 Texture Spray Discs



Easy-to-use controls.



Heavy-duty Air Spray Texture Gun.



High-output piston pump.