



## Anti-Graffiti Coating Systems

# GRAFFITI GARD® IV BIODEGRADABLE CLEANER

### DESCRIPTION

TEX•COTE® GRAFFITI-GARD® IV BIODEGRADABLE CLEANER is a proprietary, state-of-the-art, environmentally friendly, GREEN cleaner used to clean graffiti off surfaces that have been protected with TEX•COTE GRAFFITI GARD® IV GLOSS and LOW LUSTER. GRAFFITI GARD IV BIODEGRADABLE CLEANER is a non-regulated, nearly 0 VOC (<1) cleaner that effectively re-

moves graffiti safely in a short period of time without pungent odors or fumes leaving the GRAFFITI GARD IV film intact to continue protecting against graffiti.

### FEATURES

- Water-based
- pH Neutral ( 7 )
- Non-combustible / no special handling
- Clings to vertical surfaces without drips and runs
- Typically works in 15 minutes

### BENEFITS

- VOC 's <1%
- Non-hazardous / Non Toxic
- No Fumes
- Cleans graffiti off permanent anti-graffiti system.

### RECOMMENDED OVER

Use over GRAFFITI GARD® IV GLOSS and LOW LUSTER systems to remove graffiti.

### APPLICATION

**Application Equipment:** GRAFFITI-GARD® IV BIODEGRADABLE CLEANER may be applied by brush or roller. Use of a soft bristled brush for scrubbing is recommended for hard to clean areas.

**Application Rate:** Quantity of cleaner needed will depend on the amount of graffiti to be cleaned and the surface texture to be cleaned. One quart of cleaner will usually clean approximately 40-50 square feet of affected area.

**Working Times:** GRAFFITI-GARD® IV BIODEGRADABLE CLEANER should be allowed to sit on graffiti 10 minutes prior to light scrubbing with soft bristled brush. If the product dries, simple re-wet and continue with scrubbing. Use an additional 5 minute dwell time before rinsing or pressure washing for hard to clean areas.

**GRAFFITI REMOVAL:** Graffiti should be removed as soon as possible. Prolonged exposure requires more effort to remove. Spray paint graffiti should be removed

with GRAFFITI GARD® IV BIODEGRADABLE CLEANER followed by power washing.

1. Using a brush or roller, coat graffiti areas liberally with GRAFFITI GARD IV BIODEGRADABLE CLEANER.
2. Allow to sit ten ( 10 ) minutes.
3. Scrub area with a soft bristled brush. Allow an additional five ( 5 ) minute dwell time for hard to clean areas.
4. Pressure wash area.
5. A second application may be necessary for aged graffiti.

### BEST PERFORMANCE

•Conduct cleaning when temperatures are between 45—90 degrees F. Avoid freezing the product. Temperatures

above 90 degrees F may result in the product drying. If this happens simply re-wet and continue.

•Remove graffiti as soon as possible for

ease of removal.

•A second application may be necessary for aged graffiti.

### TECHNICAL DATA

- Coverage rate: 40-50 sq ft / quart
- Active ingredient: Proprietary Mixture of low toxicity components

- Weight per gallon: 8.17 Typical
- Calculated VOC: <10 grams/ Liter
- Flash Point: N/A
- Solubility in water: Complete

- Odor: Slight Almond
- pH: 7
- Appearance: Creamy Paste

### ORDER INFORMATION

**Packaging:** TEX•COTE® GRAFFITI-GARD® IV BIODEGRADABLE CLEANER is available in One ( 1 ) quart or One ( 1 ) gallon containers.

**Application Rates:** Quantity of cleaner needed will be dependent on the amount of graffiti to be cleaned and the surface substrate. One quart will clean approximately 40-50 square feet. One gallon will

clean approximately 170—190 square feet.

**Shelf Life:** Six months in unopened containers. Store indoors and maintain temperature of 45-100°F. Avoid freezing.

### SAFETY

Use protective clothes, glasses, and gloves when applying and cleaning. Use with adequate ventilation. Follow recommendations on Material Safety Data Sheet.

### VOC COMPLIANCE

All TEX•COTE® products comply with federal and state Volatile Organic Compound (VOC) rules and regulations. Please contact your nearest TCA office for assistance on the local VOC compliance in the area of intended use.



**CORPORATE OFFICES & EASTERN PLANT**  
 2422 East 15th Street Panama City, Florida 32405  
 Tel: (850) 769-0347 Fax: (850) 913-8619

**COMMERCIAL SALES OFFICE**  
 4101 Ravenswood Road, Suite 218,  
 FT. Lauderdale, Florida 33312  
 Tel: (954) 581-0771 Fax: (954) 581-9516

**WESTERN PLANT**  
 5950 S. Avalon Blvd.  
 Los Angeles, California 90003  
 Tel: (323) 233-3111 Fax: (323) 232-1071