



TEX COTE FAST DRY LATEX TRAFFIC MARKING PAINT

DESCRIPTION

TEX COTE LATEX TRAFFIC PAINT is a fast drying paint to be used for markings on road ways, parking lots and airports and other areas where such markings are required. Traffic beads may be dropped into the coating while still wet to provide a light reflective marking.

FEATURES

- Fast Dry
- Easy Application
- Water clean-up
- High performance water-based coating system
- Long lasting durability
- VOC <100 grams/liter

WHERE TO USE

For marking airfields, highways, parking lots any interior or exterior horizontal asphalt or concrete surfaces where needed.

APPLICATION

TEX COTE LATEX TRAFFIC PAINT MAY BE APPLIED BY AIRLES SPRAY, BRUSH OR ROLLER. Do not apply when air or surface temperatures are below 50°F. Do not apply to extremely hot surfaces (>110°F). Do not apply when rain is forecast or humidity is above 85%.

Application Equipment: Hand or automatic line marking equipment is preferred but material can also be applied by brush, roller or conventional airless spray. Avoid the use of galvanized, brass, copper or aluminum spray equipment as clogging may occur. Thinning normally is not needed, if needed, thin only sparingly using clean water. Thinning may have the adverse effect of extending cure time. Stir thoroughly before and during use.

Surface Preparation: All surfaces must be dry, cured, solid, free of dust, dirt, oil and grease, wax, chalk, mildew or any other foreign contamination which can

adversely affect adhesion. Asphaltic seal coats should be allowed to dry at least 48 hours before applying Tex-Cote Latex Traffic Paint. Asphalt surfaces require aging before coating.

Theoretical spread Rates:
15 wet mils
4 " Line 350-450 Ft/gallon
6 " Line 250-300 Ft/gallon

Actual rate will depend on substrate texture, application method, waste, and surface porosity. Suggested theoretical rates have not taken into account these factors.

Cautions;

Danger! Vapor Harmful, may cause eye irritation, may be fatal or cause blindness if swallowed. Contains Methanol & crystalline silica. Use only with adequate ventilation. Do not breathe dust, vapors or mist. Avoid contact with eyes, skin and clothing, NIOSH approved respirator is recommended during application. Refer to SDS sheet before use.

Product Specifications

Resin Type:	Fast Dry Acrylic
Colors available:	White, Yellow, Black, Red, Safety Blue.
Gloss:	<3 60° (Flat)
Density:	13-14 #/gallon
Solids by Weight %:	72-78
Solids By Volume %:	60-62
VOC grams/liter:	<100
Theoretical Coverage Rate, 15 wet mils:	100-120 sq ft
Dry time:	
No Pick-up:	20 minutes
Full cure:	7 Days
Clean-up:	Water
Shelf Life:	1 year
Sizes Available:	Fives, 50 gallon Drums, 250 Gallon Totes
Qualifications:	