



# TY•COTE PIGMENTED

## DESCRIPTION

TY-COTE PIGMENTED protects old paint from solvents in the TEX•COTE® GRAFFITI GARD® IV FINISH COAT and can match customer's specified color. ( Must create a continuous pinhole free film. )

## FEATURES

- Urethane acrylic dispersion
- Pigmented coating for consistent color
- Water based

## RECOMMENDED OVER

Previously painted surfaces, concrete, TEX•COTE® XL-70®, masonry, architectural concrete, and other approved manufacturer's surfaces.

## BENEFITS

- Provides sleek base for anti-graffiti system

## APPLICATION

### Surface Preparation

All surfaces must be sound, and cleaned with a manufacturer approved detergent, or adequately sandblasted, wire brushed, scraped or cleaned with a suitable alternative. Such surface contaminants as dust, environmental dirt, mildew, form oils and loose substrate shall be thoroughly removed by sandblasting, water-blasting, sanding or wire-brushing as required by the manufacturer.

Allow a 28 day cure on new concrete prior to the application of TY-COTE PIGMENTED.

**CAUTION:** TY-COTE must cure a minimum of 24 hours prior to application of GRAFFITI GARD® IV or SACRIFICIAL GRAFFITI GUARD®.

### Application Rate

200 square per gallon. Consult the more detailed TEX•COTE® GRAFFITI GARD® IV SYSTEM technical data for specific substrate. Coverage rates may vary due to wall surface texture and porosity. Highly porous surfaces may require additional coats.

### Application

Apply TY-COTE PIGMENTED to clean and dry substrate using a commercial grade airless with a 0.015 to 0.017 spray tip. To prevent lap marks, avoid starting and stopping midway on walls. On large areas, two people spraying simultaneously are recommended to avoid lap marks and spray patterns.

TY-COTE PIGMENTED may also be applied via brush or roller application. Roller should be a medium nap roller. If rolling over a textured surface, make sure roller is full for complete coverage. Apply in vertical strokes initially, then cross roll for even film, ending with vertical strokes. To prevent lap marks proceed as above and continue to a "natural break" such as panel edge, seam or corner.

### Clean-up

For wet material use water. For dry material use methyl ethyl ketone ( MEK ), xylene or toluene.

## BEST PERFORMANCE

1. TEX•COTE® TY-COTE shall be applied under ideal weather conditions.
2. Graffiti marred surfaces may need to be treated with Graffiti Stain Blocker, prior to application of pigmented TY-COTE.
3. Rain is not imminent, surfaces are not damp or frozen.
4. Temperature is within 50°F ( 10°C ) and rising to 90°F ( 32.2°C ) range.
5. Incompatible form oils, concrete curing agents, old chalking paints, laitance, etc., must be removed prior to application.
6. Retaining walls, planter boxes, etc. should be waterproofed with a below grade asphalt type sealer on side of wall exposed to back-fill.
7. TY-COTE PIGMENTED shelf life is 12 months at room temperature. Container should be stored upright, sealed airtight to prevent moisture intrusion.
8. TCA does not promote or recommend coating the sealant joints, nor is the sealant compound an approved substrate.

**TECHNICAL DATA**

Percent Solids	70.2 Typical
Volume Solids	55.4 Typical
Viscosity, Krieb Units (77°±1°F)	104+2 Typical
Base Coat	Urethane / Acrylic Base
VOC, grams/liter	<100

**ORDER INFORMATION**

**Estimated Coverage Rates**

200 square per gallon. Consult the more detailed TEX •COTE® GRAFFITI GARD® IV SYSTEM technical data for specific substrate. Coverage rates may vary due to wall surface texture and porosity. Highly porous or highly textured surfaces may require additional coats.

**Colors**

TY-COTE PIGMENTED is available in TEX •COTE® standard colors or special colors upon request. Deep tone colors subject to an upcharge.

**Packaging**

1 gallon and 5 gallon pails.

**Shelf Life**

Twelve month shelf life under the following proper conditions.

- Containers must be stored upright and airtight in a dry space.
- Maintain air temperature of 45°F – 100°F (7°C – 38°C).
- Skins formed on surface of material must be removed prior to moving containers or mixing.

**SAFETY**

**Warning**

Use with adequate ventilation. Do not breathe spray mist or dust. Avoid contact with eye, skin and clothing. Wash thoroughly after handling.

**First Aid**

If you experience difficulty in breathing, leave area to obtain fresh air. If difficulty continues, seek medical attention. In case of eye contact, flush immediately with large quantities of water for at least 15 minutes. Seek medical attention if blurring or redness continues.

**VOC COMPLIANCE**

All TEX•COTE® products comply with federal and state Volatile Organic Compound (VOC) rules and regulations. Please contact your nearest TCA office for assistance on the local VOC compliance in the area of intended use.

**WARRANTY**

Upon completion of application of coating in accordance with the manufacturer's recommendations, Textured Coatings of America, Inc. will extend its limited commercial warranty for product replacement as a result of a defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with manufacturer's recommendations for installation. TEX•COTE® shall have no obligation to contribute or to otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty is available upon request.



**CORPORATE OFFICES & EASTERN PLANT**  
 2422 East 15th Street Panama City, Florida 32405  
 Tel: (850) 769-0347 Fax: (850) 913-8619

**COMMERCIAL SALES OFFICE**  
 4101 Ravenswood Road, Suite 218,  
 Ft. Lauderdale, Florida 33312  
 Tel: (954) 581-0771 Fax: (954) 581-9516

**WESTERN PLANT**  
 5950 S. Avalon Blvd.  
 Los Angeles, California 90003  
 Tel: (323) 233-3111 Fax: (323) 232-1071