



Primers/Block Fillers/Patching Compounds

WASH-GUARD™ TEX-BOND™ PRIMER

DESCRIPTION

WASH-GUARD™ Tex-Bond™ Primer is a water-based, ready-to-use primer specifically formulated to act as a bonding coat over difficult to adhere surfaces. WASH-GUARD™ Tex-Bond Primer utilizes state-of-the-art acrylic polymer technology designed for maximum adhesion to many hard, slick surfaces while assuring optimum adhesion of many of top-

coats applied over it.

FEATURES

- Water-based acrylic formulation.
- Superior adhesion to hard, slick surfaces.
- Fast drying
- Single component product.
- Low VOC.
- Soap and water clean-up.

- Apply by airless spray, conventional spray, brush, or roller.

RECOMMENDED OVER

- Fiberglass
- PVC
- Tile
- Paneling
- Mildly Chalking Surfaces
- Previously Painted Non-Metal Surfaces

APPLICATION

Application Equipment:

- Conventional airless spray with .013-.015 tip.
- Medium nap (3/8" - 1/2") roller.
- High-quality nylon/ polyester bristle brush.

Surface Preparation

Surface must be sound, clean and dry prior to application of primer. Remove all loose, chipping, cracking and peeling paint from previously painted surfaces by hand scrap-ing, sanding and wire brushing and/or by use of power tool cleaning methods such as electric sanders, grinders, etc. Remove any dust, dirt, grease, oils, waxes, mildew, loose rust, mill scale, rust deposits or any other surface contaminants from metal surfaces by hand or power tool cleaning according to SSPC-SP2 or SSPC-SP3 standards. **WARNING!** If you scrape, sand or re-

move old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Previously Painted or Glossy Surfaces: If in sound condition, make sure that surface is free of all contaminants. Apply a test area of the primer and allow to cure for one week, then test adhesion. If adhesion is poor, then mechanical abrasion such as sanding may be necessary followed by retesting the adhesion of the

primer.

Application:

Apply WASH-GUARD™ Tex-Bond™ Primer after the surface has been prepared according to the previous directions. If surfaces have been factory primed, advise TCA of type to avoid incompatibility and potential loss of adhesion. Apply at a coverage rate of 300-400 square feet per gallon. Allow a minimum of 24 hours to dry under ideal weather conditions prior to top-coating. Primer must be top-coated within 14 days of application or re-priming will be necessary.

Clean-Up:

Clean up wet material with soap and water.

BEST PERFORMANCE

- All surfaces must be cleaned and prepared per above instructions.
- Do not apply over damp surfaces or when rain is imminent.
- Protect product from freezing.

- If WASH-GUARD™ Tex-Bond™ Primer is not top-coated within 14 days of application, re-priming may be necessary.
- Air temperature during application shall be 45°F and rising, and not exceeding 100°F. Cooler temperatures will retard

cure of product.

- If surface has been factory primed, advise manufacturer of type used to avoid possible loss of adhesion or incompatibility.

ORDER INFORMATION

Packaging:

WASH-GUARD™ Tex-Bond™ Primer is available in one (1) or five (5) gallon containers.

Coverage Rates:

300-400 square feet per gallon depending on surface profile and application method. **Do not thin.**

Shelf Life:

Twelve month shelf under proper storage conditions. Containers must be stored upright and maintained between 40°F – 110°F. Keep away from direct sunlight.

TECHNICAL DATA

- Color: White
- Gloss: Flat
- Weight per gallon: 10.2 lbs
- Weight Solids: 41.0%
- Viscosity: 90-95 Ku
- VOC: <100 grams/ Liter
- Flash Point: None
- Shelf life: 12 months (unopened/ properly stored)
- Do not store in direct sunlight.
- Shelf life: 12 months (unopened /properly stored between 40 - 110°F temperature)
- Application Temperature: 50 - 100°F (10 - 38°C)
- Dry Time @ 77°F (25°C) & 50% RH:
 - To Touch: 1 hour
 - Recoat: 4 hours
 - Top-coating: 24 hours minimum

***High humidity and cool temperature will result in longer dry, recoat and service times. ***

SAFETY

Do not breathe spray mist. Wear appropriate gloves and eye protection during application. Wash thoroughly after handling.

First aid:

In case of eye contact, flush immediately with large quantities of water for at least 15 minutes. Seek medical attention if blurring or redness continues.

VOC COMPLIANCE

All TEX•COTE® products comply with federal and state Volatile Organic Compound (VOC) rules and regulations.

WARRANTY

Upon completion of application of coating in accordance with the manufacturer ' s recommendations, Textured Coatings of America, Inc. will extend its limited commercial warranty for product replacement as a results of a defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with manufacturer' s recommendations for installation. TEX•COTE® shall have no obligation to contribute or to otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty is available upon request.



CORPORATE OFFICES & EASTERN PLANT
 2422 East 15th Street Panama City, Florida 32405
 Tel: (850) 769-0347 Fax: (850) 913-8619

COMMERCIAL SALES OFFICE
 4101 Ravenswood Road, Suite 218,
 FT. Lauderdale, Florida 33312
 Tel: (954) 581-0771 Fax: (954) 581-9516

WESTERN PLANT
 5950 S. Avalon Blvd.
 Los Angeles, California 90003
 Tel: (323) 233-3111 Fax: (323) 232-1071