

SAFETY DATA SHEET
CoolWall® Classic Primer

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: CoolWall® Classic Primer**Product Number:** PR650-HI**Product Use:** Paint material**Manufacturer/Supplier:** Tex-Cote LLC
2422 East 15th Street,
Panama City, FL 32405**Phone Number:** 850-769-0347**Emergency Phone:** 1-800-424-9300 (CHEMTREC)**Date of Preparation:** December 13, 2019

Section 2: HAZARDS IDENTIFICATION

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).**GHS Classification:** Eye Irritant Category 2B
Skin Irritant Category 2
Carcinogenicity - Category 1A**Signal Word:** DANGER!**Hazard Statements:** MAY CAUSE EYE AND SKIN IRRITATION. MAY CAUSE CANCER**GHS Label Elements Symbol(s)****Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink or smoke when using this product. Wash hand thoroughly after handling. Take off contaminated clothing and wash it before reuse. Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations.**If in Eye:** Rinse cautiously with water for several minutes and remove contact lenses if present and easy to do. Continue rinsing and get medical attention if eye irritation persists.**If on Skin:** Wash with plenty of soap and water.**If Swallowed:** Rinse mouth and get medical attention if you feel unwell.**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.**Potential Health Effects:** **Eye:** May cause eye irritation.**Skin:** May cause skin irritation.**Ingestion:** May be harmful if swallowed.**Inhalation:** May cause respiratory tract irritation.**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause stomach distress, nausea or vomiting. Vapors may cause drowsiness and dizziness.**Medical Conditions Aggravated By Exposure:** Asthma. Allergies.**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.**Hazards Not Otherwise Classified (HNOC):** None known

SAFETY DATA SHEET
CoolWall® Classic Primer

Unknown Acute Toxicity: 42.5% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: HAZARDS INFORMATION ON INGREDIENTS

Substance/mixture: Mixture

| Ingredient | CAS # | Wt. % |
|-----------------------------|------------|---------|
| Titanium Dioxide | 13463-67-7 | 1 - 10 |
| Ground Limestone | 1317-65-3 | 30- 50 |
| Ethylene Glycol | 107-21-1 | 1 - 3 |
| Crystalline Silica - Quartz | 14808-60-7 | 0.1 - 1 |

The exact percentage (concentration) of composition has been withheld as a trade secret.

See section 8 for occupational exposure limit information

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: DO NOT induce vomiting. If victim is conscious and alert, give 2 cupfuls of water. Never give anything by mouth to an unconscious person. Seek medical attention or call poison control immediately.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately. (Show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow entering waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

SAFETY DATA SHEET

CoolWall® Classic Primer

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage: Keep out of the reach of children. Keep container tightly closed. Store in a cool place. Keep from freezing.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits:

| Ingredient | OSHA PEL, ACGIH-TLV |
|-----------------------------|--|
| Titanium dioxide | OSHA PEL: TWA: 15 mg/m ³ Total dust, ACGIH TLV: TWA:10mg/m ³ |
| Ground Limestone | OSHA PEL: TWA: 15 mg/m ³ Total dust, TWA: 5 mg/m ³ Respirable fraction NIOSH REL: TWA: 10mg/m ³ Total dust, TWA: 5 mg/m ³ Respirable fraction |
| Ethylene Glycol | OSHA PEL: CEIL 125mg/m ³ 0hr, ACGIH TLV: 125mg/m ³ 0hr |
| Crystalline Silica - Quartz | OSHA PEL: 10mg/m ³ , ACGIH TLV: 0.025mg/m ³ |

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---------------------|
| Appearance: | Milky liquid. |
| Color: | Not available. |
| Odor: | Mild odor. |
| Odor Threshold: | Not available. |
| Physical State: | Liquid. |
| PH: | 8.0 - 9.5 |
| Viscosity: | 105 - 115 KU |
| Freezing Point: | Not available. |
| Boiling Point: | > 100 °C (> 212 °F) |
| Flash Point: | None. |
| Evaporation Rate: | Not available. |
| Lower Flammability Limit: | Not available. |
| Upper Flammability Limit: | Not available. |
| Vapor Pressure: | Not available. |
| Vapor Density: | Not available. |
| Specific Gravity: | 1.42 |
| Solubility in Water: | Dispersible. |
| Coefficient of Water/Oil Distribution: | Not available. |

SAFETY DATA SHEET

CoolWall® Classic Primer

Auto-ignition Temperature: Not available.
Percent Volatile, wt. %: Not available.
VOC content: Coatings VOC: 84 grams/liter; Material VOC: 43 grams/liter
 Maximum 100 grams/liter

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.
Conditions of Reactivity: Heat. Incompatible materials.
Incompatible Materials: Alkalis. Strong acids. Oxidizers.
Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.
Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

| Ingredient | LD ₅₀ (oral) | LD ₅₀ (Dermal) | LC ₅₀ (Inhalation) |
|-----------------------------|-------------------------|---------------------------|-------------------------------|
| Titanium dioxide | > 10000 mg/kg, rat | > 10000 mg/kg, rabbit | > 6.82 mg/L, Rat 4hr |
| Ground Limestone | 6450 mg/kg, rat | Not available | Not available |
| Ethylene Glycol | > 4000 mg/kg, rat | > 2000 mg/kg, rabbit | Not available |
| Crystalline Silica - Quartz | >22500 mg/kg, rat | Not available | Not available |

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin: May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
Inhalation: May cause respiratory tract irritation. Vapors may cause drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.
Chronic Effects: Hazardous by WHMIS criteria.
Carcinogenicity: Hazardous by WHMIS criteria.

| Ingredient | Chemical Listed as Carcinogen or Potential Carcinogen* |
|-----------------------------|--|
| Titanium dioxide | G-A4, I-2B |
| Ground Limestone | Not Listed |
| Ethylene Glycol | Not Listed |
| Crystalline Silica - Quartz | G-A1, I-1, N-1 |

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS criteria.
Reproductive Effects: Not hazardous by WHMIS criteria.
Developmental Effects:
 Teratogenicity: Not hazardous by WHMIS criteria.
 Embryotoxicity: Not hazardous by WHMIS criteria.
Respiratory Sensitization: Not hazardous by WHMIS criteria.
Skin Sensitization: Not hazardous by WHMIS criteria.
Toxicologically Synergistic Materials: Not available.

SAFETY DATA SHEET

CoolWall® Classic Primer

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations. Do not empty into drains.

Section 14: TRANSPORTATION INFORMATION

US DOT, CANADA TDG Surface: Not regulated

TRANSPORT BY SEA IMDG / IMO: Not regulated

AIR TRANSPORT ICAO-TI / IATA-DGR: Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Ethylene glycol CAS-No.107-21-1

SARA 311/312 Hazard Categories: Acute health hazard, Chronic health hazard

California Proposition 65: WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Ethylene glycol CAS-No.107-21-1

Crystalline Silica – Quartz CAS-No.14808-60-7

MA, PA, NJ Right to know Components: Ethylene glycol CAS-No.107-21-1

Crystalline Silica – Quartz CAS-No.14808-60-7

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Global Inventories

| Ingredient | DSL / NDSL |
|-----------------------------|------------|
| Titanium dioxide | DSL |
| Ground Limestone | NDSL |
| Ethylene Glycol | DSL |
| Crystalline Silica - Quartz | DSL |

HMIS - Hazardous Materials Identification System

Health - 1*

Flammability - 0

Physical Hazard - 0

PPE – H

NFPA - National Fire Protection Association:

Health - 1

Fire - 0

Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class D2A - Carcinogenicity

Class D2A - Chronic Toxic Effects

WHMIS Hazard Symbols:

SAFETY DATA SHEET
CoolWall® Classic Primer



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

| |
|--------------------------------------|
| Section 16: OTHER INFORMATION |
|--------------------------------------|

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Version #: 1.2

Prepared by: Tex-Cote LLC
Phone: (850) 769-0347
www.texcote.com