## GRAFFITI GARD®

PERMANENT AND SACRIFICIAL ANTI-GRAFFITI COATINGS

## **GRAFFITI GARD® IV Low Luster**

TEX-COTE® GRAFFITI GARD® IV Low Luster is a permanent, two-component, water-based high-performance aliphatic urethane hybrid coating available in clear or pigmented that resists graffiti from a variety of materials including spray paints and marking pens. In many cases, freshly applied wet spray paint/ink will actually crawl back on to itself, frustrating the would-be tagger into stopping and moving on to another target. The slick surface is easy to clean with graffiti removing cleaners such as TEX-COTE® "Biodegradable Graffiti Remover" followed by power washing. TEX-COTE® GRAFFITI GARD® IV is also available as a clear, higher gloss coating with the same anti-graffiti properties. Abrading the surface with light sanding or steel wool is necessary prior to repainting GRAFFITI GARD® IV surfaces.

## GRAFFITI GARD® S

TEXCOTE® GRÁFFITI GARD® S is a permanent, one-compound, ready-to-use high performance polysiloxane hybrid coating that resists graffiti from a variety of materials including spray paints and marking pens. In many cases, freshly applied wet paint/ink will actually crawl back on to itself, frustrating the would-be tagger into stopping and moving on to another target. The slick surface is easy to clean, in most cases, with a simple power washing. Depending on the age of the graffiti, graffiti removing cleaners such as TEX-COTE® "Biodegradable Graffiti Remover" may be necessary, followed by power washing. GRAFFITI GARD® S has a VOC of 240 g/L, so may not be available in certain areas due to local regulations. It is not available in California's SCAQMD district.

## SACRIFICIAL GRAFFITI GARD®


TEX-COTE® SACRIFICIAL GRAFFITI GARD® is a specially formulated and blended water-based resin for optimum performance as a protective sacrificial system over new or previously painted substrates. Sacrificial GRAFFITI GARD® may be removed with a hot water blaster with water temperature of 170° F - 180° F.




Spray paint graffiti applied to surface with GRAFFITI GARD® IV Low Luster.



GRAFFITI GARD® Biodegradable stripper applied one week after graffiti application.



Graffiti removal using power washer.



Clean surface after removal of graffiti.







